

SAFETY DATA SHEET

Tool Steel Holders

Date Created: October 12, 2009

Latest Revision No: 8

Latest Revision: April 30, 2024

Section 1 - Chemical Product and Company Identification

Material Name: All Turning, Grooving, Milling, Threading and Boring Tool Holders.
Chemical Formula: C, Cr, Fe, Mn, Mo, P, Si, S, V (See also Section 3)
CAS No. See Section 3
Manufacturer: Iscar Ltd.
 Box 11, Tefen 24959 ISRAEL
 Tel: +972 3 5680068 Fax: +972 3 6240443
 Email: IscarTelAviv@iscar.co.il
 Website: www.iscar.com

Section 2 - Hazards Identification

2. Hazard Identifications

2.1 Classification in according with EC No 1272/2008 [CLP]:

Respiratory sensitization, Inhalation (category 1)

Acute toxicity, Inhalation (Category 4)

Flammable solids (Category 2)

Chronic hazards to the aquatic environment (Category 1)

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word: **Danger**

Hazard statements:

H228 – flammable solid

H260 – in contact with water releases flammable gases which may ignite spontaneously

H317 – may cause an allergic skin reaction

H332 – harmful if inhaled

H334 – may cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 – suspected of causing cancer by inhalation

H372 – causes damage to organs (respiratory system, skin) through prolonged or repeated exposure

H410 – very toxic to aquatic life with long lasting effects

Precautionary statements:

P201 – obtain special instructions before use

P210 – keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P223 – do not allow contact with water.

P280 – wear protective gloves\protective clothing\eye protection\face protection

P260 - do not breathe dust.


P271 Use only outdoors or in a well-ventilated area.

P273 – avoid release to the environment

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P405 – store locked up

P501 – dispose of contents\container to an approved waste disposal plant

NFPA labelling:

All Tools Holders in their solid state and under normal conditions do not present an inhalation, ingestion or skin hazard. However, operations resulting in fume or dust formation such as welding, sawing, brazing, grinding, and machining may present health hazards.

Potential Health Effects

Primary Routes of Entry: Inhalation and skin contact.

Chronic Health Effects: Chronic and prolonged inhalation of high concentrations of fumes or dust of the following elements may lead to the conditions listed:

Chromium - various forms of dermatitis, inflammation and/or ulceration of the upper respiratory tract and possibly cancer of nasal passages and lungs. Based on available information, there does not appear to be any evidence that exposure to welding fume induces human cancer.

Iron (as an iron oxide)- prolonged exposure may produce pulmonary effects and/or Siderosis.

Manganese- bronchitis, pneumonitis, lack of coordination.

Vanadium (as vanadium pentoxide)- eye and respiratory tract irritant.

Acute Health Effects: Excessive inhalation of metallic fumes and dusts may result in irritation of eyes, nose, and throat. High concentrations of fumes and dusts of iron oxide, manganese may result in metal fume fever. Typical symptoms consist of a metallic taste in the mouth, dryness and irritation of the throat, chills, and fever. These symptoms may persist from 12 to 48 hours.

Carcinogenic Assessment:Chromium

ACGIH A4 - Not classifiable as human carcinogen.

IARC GROUP 3 -Unclassifiable as to carcinogenicity to humans.

Section 3 - Composition / Information on Ingredients

<u>Substance Name</u>	<u>Chemical Formula</u>	<u>CAS No.</u>	<u>EC No.</u>	<u>W/W %</u>	<u>OSHA PEL (mg/m3)</u>	<u>ACGIH TLV-TWA (mg/m3) ***</u>
Carbon/ Diamond	C	7440-44-0	231-153-3	0.32-0.45	Not established	Not established
Chromium	Cr	7440-47-3	231-157-5	0.7-5.5	1 mg/m3	0.5 mg/m3
Iron	Fe	7439-89-6	231-096-4	Balance	10 mg/m3	5 mg/m3
Manganese	Mn	7439-96-5	231-105-1	0.2-0.8	0.2 mg/m3	0.1 mg/m3
Molybdenum	Mo	7439-98-7	231-107-2	0.2-1.75	15 mg/m3	3 mg/m3 (R)
Phosphorous	P	7723-14-0	231-768-7	0.035 Max	0.1 mg/m3	0.1 mg/m3
Silicon	Si	7440-21-3	231-130-8	0.15-1.25	5 mg/m3	5 mg/m3
Sulfur	S	7704-34-9	231-722-6	0.035 Max	Not established	0.25 ppm as sulfur dioxide
Vanadium	V	7440-62-2	231-143-9	0.8-1.2	Not established	Not established

*** Last updating of Threshold Limit Values by ACGIH –2023

<u>Substance Name</u>	<u>H-Statements</u>
Chromium	Resp. Sens 1: H334, Skin Sens. 1: H317
Iron	Flam. Solid. 2: H228
Manganese	Flam. Solid. 2: H228
Molybdenum	Water-react. 1: H260
Phosphorous	Flam. Solid. 2: H228, Acute Tox. 3, Aquatic. Chronic 3: H228, H402, H412
Silicon	Flam. Solid.: H228
Sulfur	Skin Irrit. 2: H315

Section 4 - First Aid Measures

- Inhalation:** If symptoms of pulmonary involvement develop (coughing, wheezing, dyspnea, etc.) remove the exposed person to fresh air immediately; restore and/or support his or her breathing as needed. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. If symptoms persist, keep affected person warm and at rest. Seek medical attention immediately.
- Eye Contact:** If irritation occurs, remove contact lenses at once. Flush eyes immediately, including under the eyelids, gently but thoroughly, with plenty of running water for at least 15 minutes. If irritation persists, seek medical attention.
- Skin Contact:** If irritation or rash occurs, remove contaminated clothing and thoroughly wash the affected area with soap and water. If irritation or rash persists, seek medical attention.
- Ingestion:** If swallowing of greater than trace amounts is suspected, seek medical attention immediately. If the person is conscious, immediately give person large amounts of water. Induce vomiting only if specifically instructed by a physician. Caution: Never give anything by mouth to an unconscious or convulsing person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire Fighting Measures

Flash Point	N/A	
Auto-Ignition Temperature	N/A	NFPA 2 : 1 : 0
LEL	---	
UEL	---	

Extinguishing Media: For dust fires, use dry powder or sand.

Unusual Fire or Explosion Hazards: Dusts may present a fire or explosion hazard under rare favoring conditions of particle size, dispersion, concentration, a static discharge or strong ignition source. However, this is not expected to be a problem under normal handling conditions.

Special Fire-Fighting Procedures: For a dust fire confined to a small area, use a respirator approved for toxic dusts and fumes. For a large tool steel fire, use a self-contained breathing apparatus. See Section 3 and 8 for specific hazard identification and exposure control measures.

Fire-Fighting Equipment: For a powder fire confined to a small area, use a respirator approved for toxic dusts and fumes. For a large fire, fire fighters should use NIOSH/MSHA approved full-face-piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout gear. See Sections 3 and 8 for specific hazard identification and exposure control measures.

Hazardous Combustion Products: Respirable metal oxide fume, carbon dioxide and carbon monoxide. See Section 3 for specific hazard identification.

Section 6 - Accidental Release Measures

Spill/Leak Procedures: Do not walk through or otherwise scatter or disperse spilled material. Ventilate area of spill. Clean up area using methods which avoid dust generation such as a high efficiency, particulate air (HEPA) vacuum (with appropriate filter to prevent airborne dust levels which exceed the PEL or TLV), wet dust mop or wet clean-up. Use an appropriate National Institute of Occupational Safety and Health (NIOSH)-approved respirator whenever airborne concentrations of hazardous components exceed exposure limits listed in Section 8.

Section 7 - Handling and Storage

Under normal operating conditions, the use of tool steel products do not require special safety precautions beyond normal safety procedures for handling and using cutting tools, such as safety glasses with side shields and approved gloves. Operations such as grinding, cutting, burning, and welding of tool steel products may generate excessive heat as well as dust or fumes that may require special handling procedures.

Hygienic Practices: Wash hands thoroughly after handling and before eating, smoking, using the toilet or applying cosmetics. Wash all exposed skin at the end of the work shift. The consumption of food and beverages as well as smoking should be prohibited in areas where hazardous components may be present. Do not shake clothing, rags, or other articles to remove dust. Dust should be removed from clothing, rags or other articles by laundering or vacuuming (with the appropriate filters).

Handling and Storage Precautions: Maintain good housekeeping procedures to prevent dust accumulation, especially during grinding. Avoid dust inhalation and direct skin or eye contact with dust. See Section 3 for specific health hazards. Store in a cool, dry, well-ventilated area. Keep away from sparks or ignition source. Keep away from strong acids and strong oxidizers.

Other Precautions: Always perform clean up operations using methods that avoid dust generation such as a HEPA vacuum, wet dust mop or wet clean-up. Use an appropriate NIOSH-approved respirator whenever airborne concentrations of hazardous components exceed exposure limits listed in Section 2.

Comments: Periodic health monitoring is suggested for individuals regularly exposed to dust or fumes, with particular attention to any potential sensitization effects of such materials.

Section 8 - Exposure Controls/Personal Protection**Threshold values:**ChromiumOSHA-PEL 1 mg/m³ACGIH-TLV 0.5 mg/m³ (TWA)IronOSHA-PEL 10 mg/m³, fume as Fe₂O₃ACGIH-TLV 5 mg/m³, fume/dust as Fe₂O₃ManganeseOSHA-PEL 5 mg (Mn)/m³ (CEIL)ACGIH-TLV 0.02 mg (Mn)/m³ (TWA), fumeMolybdenumOSHA-PEL 15 mg/m³, dustACGIH-TLV 3 mg/m³ (TWA), fumeACGIH-TLV 10 mg/m³ (TWA), as dustPhosphorousOSHA-PEL 0.1 mg/m³ACGIH-TLV 0.1 mg/m³ (TWA)SiliconOSHA-PEL 15 mg/m³, dustOSHA-PEL 5 mg/m³, fumeSulfurOSHA-PEL 13 mg/m³, as sulfur dioxideACGIH-TLV 0.25 mg/m³ (TWA)VanadiumOSHA-PEL 0.5 mg/m³ (CEIL), dust as V₂O₅OSHA-PEL 0.1 mg/m³, fume as V₂O₅ACGIH-TLV 0.05 mg/m³, dust/fume as V₂O₅**IDLH: (Immediately Dangerous to Life and Health)*:****Chromium:** 25 mg Cr(III)/m³**Manganese:** 500 mg Mn/m³**Molybdenum:** 5000 mg/m³ (as Mo)**Phosphorous (yellow):** 5 mg/m³

*ONLY FOR DUST

Ventilation: Provide local exhaust ventilation or general dilution ventilation to maintain exposure levels below TLV TWA.**Protective Clothing and Equipment:** Wear safety glasses with side shields when grinding or cutting tool steel products. Wear protective gloves (leather or rubber) or barrier cream, and protective clothing to prevent skin contact with dusts. See Section 3 for specific health hazards.**Respirator:** Use a NIOSH-approved respirator with a HEPA cartridge whenever airborne concentrations of hazardous components exceed exposure limits listed in Section 2.**Contaminated Clothing and Equipment:** Soiled clothing should be laundered separately. Dust should be removed by water wash or vacuuming with the appropriate filters. Do not shake clothing, rags, or other items to remove dust.**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State	Solid
Color	Gray black with metallic luster
Odor	Odorless
Vapor Pressure (mm Hg)	Not applicable
Vapor Density (Air = 1)	Not applicable
Percent Volatile by Volume	Not applicable
Water Solubility	Insoluble
Specific Gravity (H₂O=1)	Not applicable
Boiling Point	Not applicable
Evaporation Rate	Not applicable

Section 10 - Stability and Reactivity

Stability: The product is stable under normal use conditions

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities: Strong acids. Contact of dust with strong oxidizers may cause fire or explosions.

Conditions to Avoid: Not known.

Hazardous Decomposition Products: Respirable metal oxide fume.

Section 11 - Toxicological Information

Carbon:	LD ₅₀ (Oral Rat) 10,000 mg/kg	Iron:	LD ₅₀ (Oral rat) 30,000 mg/kg
Manganese:	LD ₅₀ (Oral rat) 9000 mg/kg		
Molybdenum:	LD ₅₀ (Oral rat) 5000 mg/kg LD ₅₀ (Dermal rat) 2000 mg/kg	Phosphorous :	LD ₅₀ (Oral rat) 15,000 mg/kg
Silicon:	LD ₅₀ (Oral rat) 3160 mg/kg LD ₅₀ (Dermal rabbit) 5000 mg/kg	Vanadium:	LD ₅₀ (Oral rat) 2000 mg/kg

Section 12 - Ecological Information

The product may cause an environmental risk including damage to water sources and soil pollution.

Section 13 - Disposal Consideration

Disposal: Consider recycling. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

Sea (IMO / IMDG)	Shipping Name:	Not regulated
Air (ICAO /IATA)	Shipping Name:	Not regulated
European Road / Rail (ADR/RID)	Shipping Name:	Not regulated
U. S. Department of Transportation	Shipping Name:	Not regulated
Canadian Transportation of Dangerous Goods	Shipping Name:	Not regulated

Section 15 - Regulatory Information

EPA and OSHA Designations:

Regulation (EC) No 1272/2008 [CLP]

European Directive 67/548/EEC

labeling in accordance with GHS:

Regulation (EC) No 1272/2008 [CLP]

European Directive 67/548/EEC

Signal word: Danger

During normal operation and usage, tool holders products do not present ingestion, or other chemical hazards of any kind. However, operations such as grinding, cutting, or heating these products may produce or release dust, fumes or vapors of potentially hazardous ingredients, which can be swallowed, inhaled or come in contact with the skin and/or eyes and may present health hazards, if the exposure limits described in Section 8 are exceeded. These products are cutting tools which may contain sharp edges.

Cutting tools can break during normal usage. To avoid injury, equipment with guards and safety shields should be used.

This product contains chromium, cobalt, and/or nickel, which are listed in California Proposition 65 as known cancer-causing chemicals.

Section 16 - Other Information

This product, to the best of our knowledge and belief, does not contain and is not manufactured with any Class I or Class II Ozone Depleting Chemicals (ODCs).

Disclaimer: This Material Safety Data Sheet and the information it contains is consistent with recommended applications of these products and anticipated non-routine activities involving the products. It is the user's responsibility to identify and protect against health and safety hazards presented by modification of all Turning, Grooving, Milling, Threading, and Boring Tool Holder products after manufacture. Individuals handling all Turning, Grooving, Milling, Threading, and Boring Tool Holder products or powders should be informed of all relevant hazards and recommended safety precautions and should have access to the information contained in this MSDS.

The details contained in this SDS are believed to be accurate and based on our recent state of knowledge and experience. However, ISCAR make no claim regarding the accuracy or completeness of the information and assume no liability for any loss, damage or injury of any kind which may result from or arise out of the use of or reliance on the information contained in the SDS by any person or entity.